



ULTRA-POLY CORPORATION

PIONEERING PLASTICS RECYCLING THROUGH INNOVATION

102 DEMI ROAD, PORTLAND, PA 18351 • (570) 897-7500 • TOLL FREE (800) 932-0619

TECHNICAL DATA SHEET

PolyEdge^{PIR}

UP1000 LD-INJ

*Low Density Polyethylene
Injection Grade*

UP1000 LD-INJ is a recycled, low density polyethylene compound intended for injection applications.

Typical Properties

	<u>Test Method</u>	<u>Result</u>	<u>Units</u>
Melt Flow	ASTM D1238	6.0 – 12.0	g / 10 minutes
Specific Gravity	ASTM D792	0.91 – 0.95	
Flexural Modulus	ASTM D790	40,000 – 70,000	psi
Tensile Strength	ASTM D638	1,000 – 1,800	psi
Ash	ASTM D5630	3 – 7	wt. %

As a full service compounder, Ultra-Poly can produce grades to meet application specific property profiles. For further details, please contact your local Ultra-Poly sales representative or call 1-800-932-0619 or email Info@Ultra-Poly.com.

The information contained on this data sheet was generated by Ultra-Poly Corporation utilizing the identified industry standard testing procedures. This data is “typical data” and is expressly not intended to be a certification of any kind. This data is not intended to be used as a design specification. The suitability of this material for any application can only be determined by the developer of that application by actually testing the material in that application. **DO NOT USE THESE MATERIALS FOR ANY MEDICAL DEVICE OR COMPONENT, OR FOR ANY FOOD CONTACT APPLICATIONS.**