

**ULTRA-POLY CORPORATION**

PIONEERING PLASTICS RECYCLING THROUGH INNOVATION

102 DEMI ROAD, PORTLAND, PA 18351 • (570) 897-7500 • TOLL FREE (800) 932-0619

## TECHNICAL DATA SHEET

**PolyEncore<sup>PCR</sup>**

### **UP5089 HOPP-PCR**

*Homopolymer Polypropylene Compound  
Injection Molding Grade*

UP5089 HOPP-PCR is a recycled, homopolymer polypropylene compound intended for injection molding applications that require high flow and good stiffness.

### **Typical Properties**

	<u>Test Method</u>	<u>Result</u>	<u>Units</u>
Melt Flow	ASTM D1238	45 – 55	g / 10 minutes
Specific Gravity	ASTM D792	0.890 – 0.945	
Flexural Modulus	ASTM D790	170,000 – 230,000	psi
Tensile Strength	ASTM D638	3,900 – 4,900	psi
Notched Izod Impact	ASTM D256	0.51 – 0.90	ft. * lb. / in.
Ash	ASTM D5630	2 - 9	wt. %

As a full service compounder, Ultra-Poly can produce grades to meet application specific property profiles. For further details, please contact your local Ultra-Poly sales representative or call 1-800-932-0619 or email [Info@Ultra-Poly.com](mailto:Info@Ultra-Poly.com).

The information contained on this data sheet was generated by Ultra-Poly Corporation utilizing the identified industry standard testing procedures. This data is “typical data” and is expressly not intended to be a certification of any kind. This data is not intended to be used as a design specification. The suitability of this material for any application can only be determined by the developer of that application by actually testing the material in that application. **DO NOT USE THESE MATERIALS FOR ANY MEDICAL DEVICE OR COMPONENT, OR FOR ANY FOOD CONTACT APPLICATIONS.**