



ULTRA-POLY CORPORATION

PIONEERING PLASTICS RECYCLING THROUGH INNOVATION
102 DEMI ROAD, PORTLAND, PA 18351 • (570) 897-7500 • TOLL FREE (800) 932-0619

TECHNICAL DATA SHEET

PolyExcel_{FCG}

UP1589 RCPP FDA

*Random Copolymer Polypropylene Compound
Injection Molding Grade*

UP1589 RCPP is a recycled, random copolymer polypropylene compound that is covered by an FDA NOL. This product is suitable for injection molding articles for contact with food under Conditions of Use E through G.

Typical Properties

| | <u>Test Method</u> | <u>Result</u> | <u>Units</u> |
|---------------------|--------------------|-------------------|-----------------|
| Melt Flow | ASTM D1238 | 12 – 18 | g / 10 minutes |
| Specific Gravity | ASTM D792 | 0.890 – 0.945 | |
| Flexural Modulus | ASTM D790 | 160,000 – 190,000 | psi |
| Tensile Strength | ASTM D638 | 3,200 – 4,200 | psi |
| Notched Izod Impact | ASTM D256 | 0.90 – 1.40 | ft. * lb. / in. |
| Ash | ASTM D5630 | 2 - 9 | wt. % |

As a full service compounder, Ultra-Poly can produce grades to meet application specific property profiles. For further details, please contact your local Ultra-Poly sales representative or call 1-800-932-0619 or email Info@Ultra-Poly.com.

The information contained on this data sheet was generated by Ultra-Poly Corporation utilizing the identified industry standard testing procedures. This data is “typical data” and is expressly not intended to be a certification of any kind. This data is not intended to be used as a design specification. The suitability of this material for any application can only be determined by the developer of that application by actually testing the material in that application. **DO NOT USE THESE MATERIALS FOR ANY MEDICAL DEVICE OR COMPONENT, OR FOR ANY FOOD CONTACT APPLICATIONS.**